



MATERIAL SAFETY DATA SHEET

HCFC-Free
"GREEN"
 Polyiso Roof
 Insulation

SECTION 1: Product and Company Information

**PRODUCTS: ACfoam®-III Roof Insulation;
 ACfoam®-IV Roof Insulation;
 ACfoam® Recover Board Roof Insulation;
 ACfoam® HS CoverBoard Roof Insulation**

PRODUCT DESCRIPTION AND USE:

Rigid foam insulation panels for installation as delivered over roof decks. Insulation panels consist of a flat or tapered closed-cell polyisocyanurate foam core bonded on each side to heavy cream-colored coated glass filament facer. The thickness of the foam ranges from 0.5 to 4.5 inches. Insulation panels are typically specified for mechanically attached single ply, cold-applied BUR and cold-applied modified bitumen membrane system roof coverings.

MANUFACTURER: Atlas Roofing Corporation
 2000 River Edge Parkway, Suite 800
 Atlanta, Georgia 30328
 Phone: 770-952-1442

HEALTH AND TECHNICAL CONTACTS:

From 8:00 AM to 5:00 PM (respective time zone); call one of the following numbers for the location closest to you:

- | | | |
|---|--------------|---------------------------------|
| Camp Hill, Pennsylvania
800-955-1476 | 800-688-1476 | LaGrange, Georgia |
| East Moline, Illinois
800-477-1476 | 800-677-1476 | Phoenix, Arizona |
| Northglenn, Colorado
800-766-1476 | 800-288-1476 | Diboll, Texas |
| Etobicoke, Ontario, Canada | 888-647-1476 | Delta, British Columbia, Canada |

In the event of a chemical emergency after 5:00 PM and on weekends, call CHEMTREC at 800-424-9300 or, in Canada, CANUTEC at 613-996-6666.

SECTION 2: Composition and Ingredient Information

COMMON NAME	CHEMICAL NAME	WEIGHT % IN ARTICLE‡	CAS NUMBER	
Polyiso foam, containing: Residual blowing agent	isocyanurate homopolymer	50	None	
	normal pentane	< 3	109-66-0	
Non-woven coated glass facer containing:		50	None	
	Fiberglass	continuous filament glass fibers	20	65997-17-3
	Limestone	limestone	Proprietary	1317-65-3
	Latex	polyvinyl acetate	Proprietary	9003-20-7

‡Weight % based on 1-inch foam thickness.

SECTION 3: Hazard Overview

No unusual conditions are expected from this product. Freshly expanded or heated foam may off-gas some pentane-blowing agent, which is heavier than air and may accumulate to ignitable concentrations if stored inside a sealed container or within confined areas. Ignitable atmospheres have concentrations that exceed inhalation exposure limits for workers, further reinforcing the need for ventilation when foam is freshly expanded.

With the exception of the blowing agent, these products do not present an inhalation, ingestion, or contact health hazard unless subjected to operations such as sawing, sanding, or machining that result in the generation of airborne particulates (dusts). Exposure to high dust levels may irritate the skin, eyes, nose, throat, or upper respiratory tract. Inhalation of high amounts of dust over long periods may overload lung clearance mechanisms and make lungs more vulnerable to respiratory disease. [See Section 6 of this MSDS for other health information and exposure limit standards for product ingredients.]

Canadian users: LD50 and LC50 data are listed below for those constituent(s) that data is available.

	LC50	LD50	Hodge & Sterner classes	
	mg/(m ³ air)	mg/(kg body wgt)	(inhalation)	(oral)
Pentane	364,000 (rat, inh, 4hr)	446 (mouse, i.v.)	relatively harmless	insufficient data
Calcium carbonate	Not available	64,500 (rat, oral)	insufficient data	relatively harmless
Formaldehyde	400 (mouse, inh, 2hr)	42 (mouse, oral) 100 (rat, oral)	moderately toxic	moderately toxic

SECTION 4: Fire and Explosion Hazard Data

The product is a solid article that will burn if exposed to an ignition source of sufficient heat and intensity, or open flame, such as a welder's torch. It should be installed with a 15-minute thermal barrier between it and the structure's interior. Under certain fire conditions, combustible gases can be generated, creating rapidly spreading, high-intensity flames and dense, black smoke. Burning of this product can produce irritating and potentially toxic fumes and gases, including carbon monoxide and carbon dioxide; other undetermined hydrocarbon fractions could be released in small quantities.

Flashpoint: Not applicable (product is not a liquid).
Auto-ignition temperature: Not determined.
Extinguishing media: Water spray/fog, CO₂, dry chemical (consider media appropriate for surrounding materials).
Respirator for firefighting: Self-contained breathing apparatus (SCBA).

Pentane vapors may be emitted from freshly produced foam or when product is heated. Pentane concentrations between the lower and upper explosive limits (LEL and UEL) may accumulate under unique circumstances inside a sealed container or within confined areas. If such concentrations are provided a source of ignition, there may be a very high rate of flame propagation.

Pentane: Flashpoint ≤ -37°C
Boiling point = 28 to 49°C
Vapor density = 2.49
Vapor pressure = 514 mm Hg at 25°C
LEL = 1.5% (35,000 mg/m³)
UEL = 7.8%

SECTION 5: Reactivity Data

Stability: Stable. Service temperature range: -100 to 250°F. To prevent structural deterioration, avoid contact with acetone, methyl ethyl ketone, tetrahydrofuran, chlorine, chloroform, hydrogen peroxide, ethylene dichloride, dimethyl sulfoxide, and dimethyl formamide.

Hazardous Decomposition Products: None identified.

Hazardous Polymerization: Will not occur.

SECTION 6: Health Hazard Data

Primary Means of Exposure: Inhalation of particulates
 Secondary Means of Exposure: Eye and skin contact with particulates and inhalation of vapors

INHALATION HEALTH HAZARDS:

For polyiso foams (generated dust and residual vapor)

- Acute:** Dust may cause transient mechanical irritation of the upper respiratory tract. Workplace exposures to residual pentanes from this product are expected to be below levels of any health risk. Overexposure to high concentrations of pentane can cause narcotic effects. Signs and symptoms of overexposure to pentane include headache, nausea, dizziness, difficulty walking, or sleepiness. Studies have shown that short-term (10-minute) exposures to pentane concentrations as high as 5,000 ppm (11,750 mg/m³) produced no symptoms. Workplace exposure limits are provided in table below.
- Chronic:** There is no evidence that dust from polyiso foam causes disease in humans, and no chronic effects are known for exposures to pentane.

For continuous filament glass fibers in facers (generated dust)

- Acute:** Airborne fragments of glass fibers may cause mechanical irritation of the upper respiratory tract, particularly mouth, nose and throat; glass dust may cause transient irritation of the upper respiratory tract. Workplace exposure limits are provided in table below.
- Chronic:** No chronic health effects are known to be associated with exposure to glass fibers. Results from epidemiological studies have not shown any increase in respiratory disease or cancer. The International Agency for Research on Cancer has classified continuous filament fiberglass "Not Classifiable as to Carcinogenicity to Humans" (Group 3).

For limestone and latex in facers (generated dust)

- Acute:** Dust may cause transient mechanical irritation of the upper respiratory tract. Workplace exposure limits are provided in table below.
- Chronic:** There is no evidence that dust, containing limestone or latex, causes disease in humans.

AIRBORNE EXPOSURE LIMITS:

Constituent or Category	OSHA PEL	ACGIH TLV	NIOSH REL
	(mg/m ³)	(mg/m ³)	(mg/m ³)
Nuisance dusts NOS containing no asbestos and <1% crystalline silica	15 TWA total 5 TWA respirable	10 TWA	Not applicable
Fiberglass dust	See nuisance dusts	5 TWA	Not applicable
Limestone dust	See nuisance dusts	See nuisance dusts	10 TWA total 5 TWA respirable
n-Pentane	2950 TWA	1410 TWA	350 TWA 1800 Ceiling 3525 IDLH
Formaldehyde	0.9 TWA 2.5 STEL	0.4 TWA	0.02 TWA 0.12 STEL 25 IDLH

EYE CONTACT HEALTH HAZARDS:

- Acute:** Mechanical irritation, redness, tearing, and blurred vision can occur if dusts generated from these products come into contact with eyes.
- Chronic:** None known.

SKIN CONTACT HEALTH HAZARDS:

- Acute: Direct contact with rough-cut foam or facers can cause mechanical abrasion cuts or puncture to fingers, hands or exposed skin.
Chronic: None known.

SIGNS AND SYMPTOMS OF EXPOSURE:

Irritation of the upper respiratory tract, eyes, and/or skin.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Any condition generally aggravated by mechanical irritants in the air or on the skin. Specific data are not available which address medical conditions that are generally recognized as being aggravated by exposure to this product.

CANCER-CAUSING POTENTIAL:

WARNING! This Product Contains a Chemical Known To The State of California To Cause Cancer. The warning above is provided in accordance with the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65).

FIRST AID PROCEDURES:

- Inhalation: Remove to fresh air. Drink water to clear throat and blow nose to remove dust.
Skin: Wash with soap and cool running water.
Eyes: Flush eyes with running water for at least 15 minutes. Do not rub or wipe eyes. If irritation persists, consult a medical professional.
Ingestion: Product is not intended to be ingested or eaten. If product is ingested, irritation of the gastrointestinal tract may occur, and should be treated symptomatically. Do not induce vomiting. Rinse mouth with water to remove particles, and drink plenty of water to help reduce the irritation. [No chronic effects are expected following ingestion.]

Note to Physician: This product is a mechanical irritant. It is not expected to produce any chronic health effects from acute exposures. Treatment should be directed toward removing the source of irritation with symptomatic treatment as necessary.

SECTION 7: Workplace Precautions and Control Measures for Safe Handling and Use

Ventilation: Store in a dry, well-ventilated area. Assure storage containers or areas and shipping containers are adequately ventilated. No Smoking—No Matches—No Lighters—No Welding rules should be enforced. Install according to manufacturer's recommendations.

Installation Procedure: Cutting of product should be done in a manner to reduce or control generation of airborne dusts. Avoid unnecessary dust exposures when cutting or abrading by using adequate local or general ventilation. Avoid dust contact with ignition sources. Handle product using good industrial hygiene and safety practices.

Respiratory Protection: If respiratory tract irritations occur or if any dust exposure limit is exceeded, use a respirator such as 3M Model 8271 or Model 8210, or equivalent for protection against nuisance dusts. When normal ventilation is provided to work area, no respiratory protection is needed for pentane vapor.

Protective Clothing: To avoid skin irritation from excessive dust generated during cutting operations, wear long-sleeved, loose fitting clothing, long pants, and gloves.

Eye Protection: Goggles or safety glasses with side shields are recommended.

Work Area Cleanup: Pick up large pieces; do not wash down drain. Sweep or vacuum smaller pieces into a waste container for disposal. If needed, use water spray to wet down and minimize dust generation. Do not dry sweep dust accumulation or use compressed air for cleanup.

Hygienic Practices: Exposed skin areas should be washed with soap and cool water after working with product. Clothing should be laundered separately from other clothes.

SECTION 8: Releases to the Environment and Waste Disposal

Do not discard residues into sewers, storm sewers, or surface waters. If accidentally released to a water body, material will float and disperse with wind and current; contain the material with booms and remove either manually or with a vacuum truck.

If accidentally released to land, scoop up material and put into suitable container for disposal.

Chemicals in this material are not expected to cause harm to aquatic or terrestrial plants or animals; however, fish or other animals may eat the product, which could obstruct their digestive tracts.

Be a good steward of the environment and clean up residues (some components of the product are not biodegradable).

This product, if discarded as supplied, is not considered a hazardous waste under RCRA (40 CFR 261) and may be placed directly into receptacles that will transport the waste to a municipal waste, industrial waste, or demolition waste landfill. If contact with a contaminating substance alters the material, it is the user's responsibility to determine at the time of disposal whether it meets RCRA criteria for hazardous waste. Dispose in accordance with federal, state and local regulations.

SECTION 9: Additional Regulatory Considerations

Transportation Regulations: This product is not regulated as a hazardous material in transportation.

TSCA: All chemicals in this product are listed on the TSCA Inventory. TSCA 12(b) export notification requirements do not apply to this product.

SARA TITLE III: There is no Section 302 extremely hazardous substance in this product. Reporting requirements under Sections 311, 312, or 313 do not apply. [Diisocyanate precursors do not remain in the polymer foam of this product.]

All chemicals and component categories found on state lists are addressed in this MSDS.

This product has been classified in accordance with the hazard criteria of *Canada's Controlled Products Regulations* and the MSDS contains all of the information required by said regulations. All chemical components are on *Canada's Domestic Substances List (DSL)*. Pentane is the only constituent on *Canada's Ingredients Disclosure List (IDL)* that exceeds threshold concentrations.

NFPA / HMIS Rating: Health= 1 Flammability= 1 Reactivity= 0

SECTION 10: Physical/Chemical Characteristics

The following applies to the product (article), not to pure forms of individual constituents of the product:

Appearance: White or cream-colored foam flat or tapered solid with a coated glass mat facing on each side.

PROPERTY	PROPERTY
Boiling Point (°F):NA	Specific Gravity:<1
Melting Point (°F):>250	Solubility (Water):Insoluble
Vapor Pressure:NA	Vapor Density (Air=1):NA
Percent Volatile By Volume:<1	Evaporative Rate:NA
pH:NA	Odor:Negligible
NA=not applicable	

Prepared by: Atlas Roofing Corporation