

PLIOBOND® 7008 WATER BASED  
PVC ADHESIVE 120439

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone number	1-800-ASHLAND (1-800-274-5263)
Product name	PLIOBOND® 7008 WATER BASED PVC ADHESIVE	
Product code	120439	
Product Use Description	No data	

**2. HAZARDS IDENTIFICATION**

**Emergency Overview**

Appearance: liquid  
CAUTION! Carcinogen.

**Potential Health Effects**

**Routes of Exposure**

Inhalation, Skin contact, Eye Contact, Ingestion

**Eye Contact**

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

**Skin Contact**

May cause mild skin irritation. Symptoms may include redness and burning of skin.

**Ingestion**

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

**Inhalation**

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

**Aggravated Medical Condition**

PLIOBOND® 7008 WATER BASED  
PVC ADHESIVE 120439

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: lung (for example, asthma-like conditions)

### Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

### Target Organs

No data

### Carcinogenicity

Vinyl acetate caused an increase in cancer of the nasal cavity in rats. The relevance of this finding to humans is uncertain. The International Agency for Research on Cancer (IARC) reclassified this chemical from Group 3 (not able to be classified) to Group 2B (possibly carcinogenic in humans) in 1995. This classification is based on the study in rats, along with knowledge that vinyl acetate is changed to acetaldehyde, a known animal carcinogen, in the body.

### Reproductive Hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

### Other Information

Formaldehyde has been identified as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) and the Occupational Safety and Health Administration (OSHA). Formaldehyde is irritating to the eyes, nose, throat, and airways, and can cause an allergic reaction (causes narrowing of the air passages of the lungs, sweating, flushing, hives, rapid heart rate, and lowered blood pressure). In addition, formaldehyde can cause an allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects). It is harmful if inhaled, swallowed or absorbed through skin.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
VINYL ACETATE MONOMER	108-05-4	>=0.5-<1%

## 4. FIRST AID MEASURES

Eyes

PLIOBOND® 7008 WATER BASED  
PVC ADHESIVE 120439

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

### **Skin**

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

### **Ingestion**

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

### **Inhalation**

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

### **Notes to Physician**

**Hazards:** No information available.

**Treatment:** No information available.

## **5. FIRE-FIGHTING MEASURES**

### **Suitable Extinguishing Media**

Water mist, carbon dioxide (CO<sub>2</sub>), dry chemical

### **Hazardous Combustion Products**

May form: acetic acid, acrolein, aldehydes, carbon dioxide and carbon monoxide, various hydrocarbons

### **Precautions for Fire-Fighting**

No special fire hazards are known to be associated with this product. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

## **6. ACCIDENTAL RELEASE MEASURES**

### **Personal Precautions**

No data

PLIOBOND® 7008 WATER BASED  
PVC ADHESIVE 120439

**Environmental Precautions**

No data

**Methods for Cleaning Up**

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers. Absorb liquid on vermiculite, floor absorbent or other absorbent material.

**7. HANDLING AND STORAGE**

**Handling**

No data

**Storage**

No data

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Exposure Guidelines**

**General Advice**

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

**Exposure Controls**

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

**Eye Protection**

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

**Skin and Body Protection**

PLIOBOND® 7008 WATER BASED  
PVC ADHESIVE 120439

Wear normal work clothing covering arms and legs. Wear resistant gloves such as:  
Natural Rubber Wear resistant gloves such as:

**Respiratory Protection**

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Physical state</b>	liquid
<b>Form</b>	No data
<b>Colour</b>	No data
<b>Odour</b>	No data
<b>Boiling point/range</b>	No data
<b>pH</b>	No data
<b>Flash point</b>	212.00 °F / 100.00 °C
<b>Evaporation rate</b>	No data
<b>Explosion limits</b>	No data
<b>Vapour pressure</b>	No data
<b>Vapour density</b>	No data
<b>Density</b>	1.100 g/cm <sup>3</sup>
	No data
<b>Solubility</b>	No data
<b>Partition coefficient (n-octanol/water)</b>	No data
<b>Autoignition temperature</b>	No data

**10. STABILITY AND REACTIVITY****Stability**

Stable.

**Conditions to Avoid**

None known.

**Incompatible Products**

PLIOBOND® 7008 WATER BASED  
PVC ADHESIVE 120439

Avoid contact with:, alkali metals, peroxides, strong alkalis, strong mineral acids, strong oxidizing agents

**Hazardous Decomposition Products**

May form:, acetic acid, acrolein, aldehydes, carbon dioxide and carbon monoxide, various hydrocarbons

**Hazardous Reactions**

Product will not undergo hazardous polymerization.

**Thermal Decomposition**

No data

**11. TOXICOLOGICAL INFORMATION**

**Acute Oral Toxicity**

VINYL ACETATE MONOMER                      LD 50 Rat: 2,920 mg/kg

**Acute Inhalation Toxicity**

VINYL ACETATE MONOMER                      LC 50 Rat: 3,680 mg/l,

**Acute Dermal Toxicity**

VINYL ACETATE MONOMER                      LD 50 Rabbit: 2,335 mg/kg

**12. ECOLOGICAL INFORMATION**

**Aquatic Toxicity**

**Acute and Prolonged Toxicity to Fish**

No data

**Acute Toxicity to Aquatic Invertebrates**

No data

**Environmental Fate and Pathways**

No data

PLIOBOND® 7008 WATER BASED  
PVC ADHESIVE 120439

### 13. DISPOSAL CONSIDERATIONS

#### Waste Disposal Methods

Destroy by liquid incineration in accordance with applicable regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution Company, IC&S Environmental Services Group at 800-637-7922.

### 14. TRANSPORT INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

### 15. REGULATORY INFORMATION

#### California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

ACETALDEHYDE  
FORMALDEHYDE

**SARA Hazard Classification** Chronic Health Hazard

#### SARA 313 Component(s)

VINYL ACETATE MONOMER	108-05-4	0.6%
--------------------------	----------	------

#### OSHA Hazards

Carcinogen

	Health	Flammability	Reactivity	Other
HMIS	2	1	0	
NFPA	2	1	0	

### 16. OTHER INFORMATION

**ASHLAND**  
**SAFETY DATA SHEET**

Page: 8  
Revision Date: 03/02/2007  
Print Date: 8/14/2007  
MSDS Number: R0311642  
Version: 1.

PLIOBOND® 7008 WATER BASED  
PVC ADHESIVE 120439

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).